



# ATM-RISK ASSESSMENT

<b>TASK:</b>	Use of the Telehandler	<b>RA No:</b>	ATMRA2020/044				
<b>EQUIPMENT / MATERIALS USED</b>	Telehandler						
<b>PERSONS AT RISK:</b>	<b>OPERATOR, PERSONS IN THE VICINITY, OTHER EMPLOYEES, CONTRACTORS, VISITORS, MEMBERS OF THE PUBLIC.</b> (All operatives or teams of operatives are to ensure that the daily on-site risk assessment is completed prior to commencing any work on site.)						
HAZARD / RISK	RISK LEVEL			CONTROL MEASURES	RESIDUAL RISK		
	S	L	RL		S	L	RL
Incorrect/unauthorised use, striking structures, people etc, becoming unstable Serious injury, fatality	5	3	<b>15</b>	The machine will only be used by competent persons who hold the requisite qualifications.  Operators are to make full use of the vehicles safety systems and measures at all times.  The ignition keys are to be removed from the vehicle, when it is not in use.	5	1	<b>5</b>
Slips when entering/leaving cab Cuts, abrasions	3	3	<b>9</b>	Operatives are to make full use of hand and foot holds/ladders etc, when entering and leaving the vehicle cab.  Operatives shall be required to wear suitable safety footwear when completing work activities and ensure they keep their footwear free from muck build up, to maintain good grip.	3	2	<b>6</b>
Stability on sloping ground Serious injury, fatality	5	3	<b>15</b>	Driving near ditches and banks is an obvious hazard, particularly where the surface is loose or is wet or where the edge is concealed by undergrowth.  Wherever possible, work should be planned to allow 'headlands' wide enough for safe turning.	5	1	<b>5</b>

<b>ATMRA2020/044</b>	<b>Original Author:</b>	Rob Whamond	<b>Date:</b>	01-06-2021
	<b>Reviewed By :</b>	Dale nelson	<b>Next Review Date:</b>	01-06-2022
Use the table below to calculate the severity and likelihood. (Severity X Likelihood = <b>RISK</b> )		Use the table below to indicate whether the Residual Risk Rating is:		
<b>Severity of Outcome;</b> 5 Fatality / Loss of Limb. 4 Serious Injury. 3 Moderate. 2 Minor Injuries. 1 Negligible. <b>Likelihood of Harm;</b> 5 Almost Certain , 4 Very Likely , 3 Fair Chance , 2 Remote, 1 Very Unlikely.		1 – 6 = Low Risk		Page 1 of 2
		7 – 11 = Medium Risk		
		12+ = High Risk		



# ATM-RISK ASSESSMENT

HAZARD / RISK	RISK LEVEL			CONTROL MEASURES	RESIDUAL RISK		
	S	L	RL		S	L	RL
Falling loads Serious injury, fatality	5	3	15	Where possible, loads should be secured to the forks.  These machines will only be operated by a competent person.  Loads should be transported in such a way that the driver/operator has as clear a field of vision as possible.	5	1	5
Poor maintenance leading to failure Serious injury, fatality	5	3	15	The machine will be subject to regular servicing and shall be visually inspected daily before use.  All maintenance and inspection shall be completed in accordance with the Provision and Use of Work Equipment regulation (PUWER).	5	1	5
Re-fuelling Fire, explosion, burns, serious injury, fatality	5	3	15	See <b>ATMRA2020/89</b> Re-fuelling of equipment.	5	1	5

<b>ATMRA2020/044</b>	<b>Original Author:</b>	Rob Whamond	<b>Date:</b>	<b>01-06-2021</b>
	<b>Reviewed By :</b>	Dale nelson	<b>Next Review Date:</b>	<b>01-06-2022</b>
Use the table below to calculate the severity and likelihood. (Severity X Likelihood = <b>RISK</b> )		Use the table below to indicate whether the Residual Risk Rating is:		
<b>Severity of Outcome:</b> 5 Fatality / Loss of Limb. 4 Serious Injury. 3 Moderate. 2 Minor Injuries. 1 Negligible.		1 – 6 = Low Risk		
<b>Likelihood of Harm:</b> 5 Almost Certain , 4 Very Likely , 3 Fair Chance , 2 Remote, 1 Very Unlikely.		7 – 11 = Medium Risk		
		12+ = High Risk		
Page 2 of 2				